

FS273M

A Cost-performance Solution for Robust
Metal Production

www.farsoon.com



SIMPLY METAL PRODUCTION

With an industrial-sized 275×275×355mm build envelope as well as an expanded powder feeding cylinder size, FS273M offers streamlined metal production of large volume parts with a wide range of industrial metal powder materials.

COST-PERFORMANCE

The FS273M metal laser sintering system is a high value proposition industrial production tool. Advanced digital optics system, robust controls, and truly open parameters gives users a much wider range of process capabilities. The FS273M is able to achieve highly detailed, functional parts while maintaining a price competitive advantage. Compact machine design enables denser, flexible factory layout for maximum throughput yield per floor area at an economical additive production cost.

OPERATION EASE & GOOD SERVICEABILITY

The FS273M features an integrated, long-lasting filtration system which allows extended operation time for longer builds and reducing the cost of filter changes. Other convenient features including pre-heated base plate, robust recoater operations, removable overflow containers, and a powder supply sufficient for a full build ensures ease of operation and good serviceability.



FARSOON FS273M

TECHNICAL DATA	FS273M	FS273M-2
External Dimension (L×W×H)	2315×1650×2105mm (91.1×65.0×82.9 in)	
Build Cylinder Size¹ (L×W×H)	275×275×355 mm (10.8×10.8×14.0 in) (Height incl. build plate)	
Net Weight	Approx. 2200 kg (4850.2 lb)	
Layer Thickness	0.02~0.1 mm (0.0008-0.0039 in)	
Scanning Speed²	Max. 15.2 m/s (49.9 ft/s)	
Laser Type	Single Laser, 1×500W	Dual Lasers, 2×500W
Scanner	F theta lenses or dynamic focusing system	
Inert Gas Protection	Argon/Nitrogen	
Average Inert Gas Consumption in Process	3-5 L / min	
Operating System	64 bit Windows 10	
Comprehensive Software	BuildStar, MakeStar®	
Key Software Features	Open machine key parameters, real-time build parameter modification, three-dimensional visualization, diagnostic functions	
Data File Format	STL	
Power Supply	EUR/China: 400V±10%, 3~/N/PE, 50Hz, 30A US: transformer sold with machine	
Operating Ambient Temperature	22-28°C (71.6-82.4°F)	
Materials³	316L, 17-4PH, Maraging Steel Grade 300, 420, H13, HX*, IN718, AlSi10Mg, AlMgSc, AlSi7Mg*, Ti6Al4V, TA15, CrZrCu, Pure Copper*, CoCrMo, W*, Ta*, more materials to come	

1 The functional build volume depends on the parts/materials.

2 For different industries and customer needs, this data may vary.

3 The materials marked with * are in the build process development.

Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon®, BuildStar®, MakeStar® are registered trademarks of Farsoon Technologies. Last Change: 2023-09



PART: VAPING MOLD
SYSTEM: FS273M
MATERIAL: 316L

www.farsoon.com

AMEA Farsoon Technologies Co., Ltd. | +86.731.8397.6198 | globalinfo@farsoon.com | No. 181 Linyu Road, Changsha National High-Tech Industrial Zone, Hunan, China

AMERICAS Farsoon Americas CORP. | +1 512-551-9901 | contact@farsoonam.com | 3161 Eagles Nest Street, Suite 350, Round Rock, TX 78665

EUROPE Farsoon Europe GmbH | +49 711 13796 0 | wehelpyou@farsoon-eu.com | Liebknechtstrasse 33, 70565 Stuttgart, Germany